



- Elegant and sophisticated design, add the extra value and esthetic feeling into applications
- Professional selection of engineering materials, overcome the harshest of your environment
- Friendly handling and module design, save your treasure time while installation
- Flexible and module assembly, effectively decrease the cost of stock
- Whole series slim; delicate and light, up to the requirement of protection IP40 and IP65
- Lower and flush mounting actuators, highly increase the fine appearance of your panel
- 22、 25 and 30mm mounting holes, fulfill your intentions of choice and replacement



Coding Principle

Pushbutton Switches E2P/E3P	E	2	R	1	R	1	B
-----------------------------	---	---	---	---	---	---	---

Part No.	Code Description
E	Classification : E=IP40 Standard H=IP65 Rubber-sealed
2	Mounting size : 2=22mm、 25mm Standard mounting 3= 30mm Standard mounting
R1	Reset mode : R1=Rotate to reset
R	Cap color : R=Red
1B	Contact mode : A=1NO B=1NC, provide 1A,2A,3A,4A, 1B,2B,3B,4B,AB,2A2B,3A3B,2A1B, 1A2B,3A1B,1A3B

Drawing

E2R1 Emergency Stop Switches	Drawing	Color	Reset Mode	Part No.
			rotate to reset	E2R1R□□
E3R1 Emergency Stop Switches	Drawing	Color	Reset Mode	Part No.
			rotate to reset	E3R1R□□

- Remarks:
1. □□ Contact Mode: 1A=1NO, 1B=1NC, 2A=2NO, 2B=2NC, AB=1NO+1NC and etc.
 2. Please change “E” to “H” for protection rating IP65.
 3. Please add *M in the last of order no. if you would like to change the yellow plastic front ring to the metal ring.